



High temperature materials for industrial processes

Christine Geers (CTH), Vedad Babic (CTH), Itai Panas (CTH), Gustav Sundell (CTH), Jesper Ejenstam (KTH), Peter Szakalos (KTH), Bosse Jönsson (SHT), Thomas Helander (SHT) Lars-Gunnar Johannson (CTH), Mats Halvarsson (CTH), Jan-Erik Svensson (CTH)

Energy and Materials Chalmers Teknikska Högskolan Applied Physics Chalmers Teknikska Högskolan Chemical Science and Engineering Kungliga Tekniska Högskolan









What is meant with industrial processes?

This project is dedicated to industrial processes which are running in **low oxygen** environments with other oxidants **instead** such as **carbon or nitrogen**.



Furnaces for heat treatments under inert conditions

- ,inert' conditions N₂/H₂
- high temperature 900-1200°C



Pre-reformer for fuel cell stacks

- syngas production in the prereformer (CO/H₂/H₂O)
- high temperature (600-900°C)

Project Group

Project leader: Jan-Erik Svensson, CTH

Participating companies: Sandvik Heating Technology (SHT)

Sandvik Materials Technology (SMT)

Powercell Entech

Research organizations: Chalmers, KTH

Senior researchers: JE Svensson, CTH, B Jönsson, SHT/ CTH, M Halvarsson, CTH, LG

Johansson, CTH, K Hellström CTH, I Panas, CTH, P Szakalos, KTH

Post Doc: C Geers, CTH; Gustav Sundell

PhD students: N Mortazawi, CTH, M Lindgren, CTH

Company personal: B. Jönsson, SHT, D. Chandrasekaran, SHT, E. Ström, SHT,

M. Lundberg SMT, P. Ekdunge, Powercell, J. Jyrinki, Entech

Project group: B. Jönsson, SHT, D. Chandrasekaran, SHT, E. Ström, SHT

M.Lundberg SMT, L. Kylhammar, Powercell, J. Jyrinki, Entech, JE Svensson, CTH, B Jönsson, SHT/CTH, M. Halvarsson, CTH,

LG Johansson, CTH, K. Hellström CTH P. Szakalos, KTH











Experimentalists



High temperature exposures in low oxygen activity environments




Theoretical Chemistry - DFT







High temperature exposures in low oxygen activity environments






State-of-the-art microscopy





With decreasing oxygen availability...

... the demand for a reliable oxide former increases significantly...



... while the availability of oxide formers decreases.

Focus in this project:

- ☐ Parameters that control nitridation
- ☐ Parameters that control carburization
- ☐ Support first principle project and solar project

Materials

- Kanthal APMT™
- Kanthal AF
- Nikrothal® 80
- Nikrothal 45 OC
- Nikrothal PM 58
- Model alloys

Exposure


- Stage one:
- N₂-H₂ (dry)
- N₂-H₂-H₂O
- Ar-H₂-H₂O
- Stage two:
- CO, CO₂, H₂O, H₂, (C_xH_y)

Parameters

- 900-1100°C
- Variations of dew points
- 1 day 1 month
- Preparation effects (grinding, polishing)
- cycling

Year of nitrogen – 2015 detailed

Year of carbon – 2016 preview



Materials

- alumina former
- Kanthal APMT
- Kanthal AF
- Kanthal PM 58
- chromia former
- Nikrothal 80
- Nikrothal 45 OC

For 900°C:

$$Cr \rightarrow Cr_2O_3$$

Al $\rightarrow Al_2O_3$

 $Y \rightarrow Y_2O_3$


$$p_{O2} = 10^{-24} \text{ bar}$$

 $p_{O2} = 10^{-38} \text{ bar}$
 $p_{O2} = 10^{-46} \text{ bar}$





Real-time in situ oxidation monitoring



Schematical drawings of the equipment used for all tests included in the HTC IP project and SEM top view SEM analysis of Kanthal AF exposed for 31 days at 700° C.

- Temperature is too low to cause well observable nitridation



Setup and exposure conditions




Ohrs

Evaluation conditions are:






• 100 ml/min



24hrs



168hrs


Cross sectional sample preparation

BIB (Broad Ion Beam)












To produce large cross-sectioned surface (> $4 \times 1 \text{ mm}$)

FIB (Focused Ion beam)



For more selective and site-specific cross-section (around $30 \times 50 \mu m$)










Most crack-like structure was found in connection with RE-particles -

however, the alumina scale underneath was even more pronounced.








CHALMERS UNIVERSITY OF TECHNOLOGY

BIB cross section through one chromia island




• 100 ml/min




What could be the source for the chromia island


- Cracks in the alumina scale
- Phases in the alloy with limited solubility of aluminium



CHALMERS UNIVERSITY OF TECHNOLOGY

Carbides as possible chromia island source







Exposure conditions are:


- 900°C
- PM58
- $N_2 5\%H_2$
- 100 ml/min




Oxide surface calculations








Oxide bulk calculations



Variation of the nitrogen content




There are two drivers for oxygen depletion from the chromia scale, one is the reducing hydrogen at the oxide/gas interface and the other much stronger one is aluminum at the chromia/alloy interface.



Carbon year has started - A preview:







Summary

In the case of nitridation, the way of entry towards the alloy has yet been identified as secondary oxide species in the oxide scale, here chromia embedded in alumina.

Reducing conditions allow the formation of metastable oxy-nitrides which present as one of the possible diffusion paths.

DFT techniques allow this insight which would otherwise not be detectable via microscopy.

Carburisation mechanisms will be approached in the same manner.



Thank you for your attention.

