Sulfur recirculation and improved material selection for high temperature corrosion abatement

- Investigating different aspects of corrosion memory (KME 714)



Sven Andersson

Thomas Norman Lars Mikkelsen



Ove Hauris Jespersen Niels Peder Hansen





Torbjörn Jonsson Jesper Liske <u>Loli Paz</u> Julien Phother




Søren Aakjær Jensen



Kristian Vinter Dahl Melanie Montgomery Yohanes Malede

Corrosion memory – Boiler operation history important

KCI/K₂SO₄




How will the corrosion attach be influenced by already formed deposit/microstructure/oxide scale...?






Research focus and correlation to KME goals



Sulfur recirculation




Full scale installation

KME goals:

Increase green electricity production from combustion of biomass and waste Improved fuel flexibility

Improved material design/selection

Mitigating alkali induced corrosion of high temperature steels - Change the fireside environment




Adding sulfur or sulfur-rich fuels

- Elemental sulfur
- Ammonium sufate
- Full scale installation Sulfur Recirculation?
- Municipal sewage sludge

Sulfur recirculation - full scale installation



MEC: Sulfur Recirculation since October 2016





Sulfur recirculation – deposit formation

Reference line (waste)


Recirculation line

Superheater deposits = 1,84%Cl

Superheater deposits = 0,27%Cl

Probe deposit = 2,65wt%Cl

Probe deposit = 0,08wt%Cl




Less Cl = less corrosion? and dioxin formation




Sulfur recirculation – corrosion mitigation

Material loss




Superheaters






Sulfur recirculation – corrosion mitigation Material loss

Superheaters – full scale measurements by MEC





Mitigating alkali induced corrosion of high temperature steels - Change the fireside environment



Adding sulphur or sulphur-rich fuels


- Elemental sulfur
- Ammonium sulfate
- ✓ Full scale installation Sulfur recirculation!
 - Municipal sewage sludge






Research focus

Sulfur recirculation



Full scale installation


Corrosion memory



KME goals:

Increase green electricity production from combustion of biomass and waste Improved fuel flexibility
Improved material design/selection


Changing fuel – more/less corrosive flue gas – memory effect?





Simulating


Change in fuel – more/less corrosive flue gas – memory effect?








Stainless steel








Stainless steel








Stainless steel





Corrosion memory – Environment Example of analysis

347H - Rec Ref

347H - Ref Ref








Positive memory effect!













Research focus

Sulfur recirculation



Full scale installation

Corrosion memory



KME goals:


Increase green electricity production from combustion of biomass and waste Improved fuel flexibility
Improved material design/selection





Corrosion memory - Material

Flue gas/deposit chemistry




As received microstructure

Changes of the microstructure

Microstructure – vulnerable for CI induced corrosion?

Background: Corrosion as function of chromium content





- High chromium content increases internal corrosion.
- High iron content gives high material loss.
- Chromium is good to form protective oxide but is also good at forming chlorides. Chromia is also broken down by formation of K₂CrO₄.
- Increased temperatures results in evaporation of metal chlorides.






Material	Condition	Time and Temperature	Exposure environment
Modified	As-received	168 h,	5%O ₂ + 15% H ₂ O + N ₂
310		at 600ºC	5%O ₂ + 15% H ₂ O + N ₂ + KCl
			deposit
	Aged at 700°C for 10,000 hours		5%O ₂ + 15% H ₂ O + N ₂
			5%O ₂ + 15% H ₂ O + N ₂ + KCl
			deposit
TP347H	As received		5%O ₂ + 15% H ₂ O + N ₂
FG			5%O ₂ + 15% H ₂ O + N ₂ + KCl
			deposit
	Exposed for 100000 hours in coal		5%O ₂ + 15% H ₂ O + N ₂
	fired plant with steam		5%O ₂ + 15% H ₂ O + N ₂ + KCl
	temperature 535°C		deposit

Microstructures of modified 310 before corrosion exposure




Why specifically this steel?

It allows testing the same material in to two widely different microstructure conditions



Deeper attack on heat treated modified 310











Corrosion memory - Material





As received microstructure

Changes of the microstructure

Microstructure – vulnerable for Cl induced corrosion!

Summary

- The Sulfur Recirculation technique successful for decreasing corrosion of superheaters.
- Corrosion memory environment:
 - Memory effects observed
 - Stronger effect on stainless steels
 - Less corrosion starting with good fuel/deposit
 - No/negative effect starting with a corrosive deposit?
- Corrosion memory material:
 - Memory effect observed
 - Microstructure vulnerable for Cl induced corrosion!

KME goals:

Increase green electricity production from combustion of biomass and waste Improved fuel flexibility
Improved material design/selection



COMBINED HEAT & POWER PLANT

BIOGAS PLANT



Sven Andersson

Thomas Norman Lars Mikkelsen

Orsted

Søren Aakjær Jensen



MAABJERG ENERGY CENTER
HOLSTEBRO STRUEF

Ove Hauris Jespersen Niels Peder Hansen



Torbjörn Jonsson Jesper Liske Loli Paz

Julien Phother



Rristian Vinter Dahl
Melanie Montgomery
Yohanes Malede